Serial No.: 10/598,282 Docket No.: 66352-048

IN THE CLAIMS:

1. (Currently Amended) Assembly comprising a water turbine and a

rotary electrical generator, the rotor of which is connected to the turbine,

which turbine comprises at least three axially directed blades

characterized in that wherein each blade is individually directly connected

to the rotor of the generator.

2. (Previously Presented) Assembly according to claim 1, wherein

the turbine comprises a first group of blades directed towards a first

direction from the rotor and a second group of blades directed towards

the opposite direction from the rotor, with each group comprising at least

3 blades.

3. (Previously Presented) Assembly according to claim 2, wherein

each blade in the first group is arranged in coalignment with a blade in

the second group.

4. (**Previously Presented**) Assembly according to claim 3, wherein

blades located in coalignment are directly mechanically connected to each

other.

5. (Previously Presented) Assembly according to claim 1, wherein

each blade is stayed by stay means.

6. (**Previously Presented**) Assembly according to claim 5, wherein

the stay means comprises elements that connect blades to each other.

- 2 -

Serial No.: 10/598,282 Docket No.: 66352-048

7. (**Previously Presented**) Assembly according to claim 6, wherein the stay means comprises an element directed radially inward from the respective blade, a radially innermost end of each element being connected to each other.

- 8. (**Currently Amended**) Assembly according to claim 6, characterized in thatwherein the stay means comprises elements extending between each blade adjacent in the circumferential direction.
- 9. (**Currently Amended**) Assembly according to any one of claims 1-8, characterized in that <u>claim 1</u>, wherein each blade (5) is connected to the rotor via a joint device (10).
- 10. (**Currently Amended**) Assembly according to any one of claims 1-9, characterized in thatclaim 1, wherein the rotor (4) comprises permanent magnets (21).
- 11. (**Currently Amended**) Assembly according to any one of claims 1

 10, characterized in that claim 1, wherein the stator (3) is encapsulated in a waterproof house.
- 12. (**Currently Amended**) Assembly according to any one of claims 1-11, characterized in that<u>claim 1, wherein</u> the rotor is situated radially outside the stator and in the same axial plane as the stator.
- 13. (**Currently Amended**) Assembly according to any one of claims 1-12, characterized in that<u>claim 1, wherein</u> the stator is wound with a high-

Serial No.: 10/598,282

Docket No.: 66352-048

voltage cable provided with a core (31) of conducting material, a first layer (32) of semiconducting material surrounding the conducting material, a layer (33) of insulating material surrounding the first layer (32) and a second layer (34) of semiconducting material surrounding the

13, characterized in that claim 1, wherein the stator (3) of the generator is

(Currently Amended) Assembly according to any one of claims 1

rotatable and connected to a turbine (22) arranged to rotate the stator

(3)-in the opposite direction to the rotor-(4).

(Currently Amended) Assembly according to any one of claims 1 15.

14, characterized in that claim 1, wherein the stator (9) is wound for

three-phase.

16. (Canceled)

insulating material.

14.

(**New**) A method of generating electric current which comprises the 17.

steps of:

providing an assembly comprising a water turbine and a rotary electrical generator, the rotor of which is connected to the turbine, which turbine comprises at least three axially directed blades wherein each blade is individually directly connected to the rotor of the generator, and placing said assembly in an underwater current.

- 4 -